

## SUS304

## フラットバー

●=コールド ●=HL ●=#400 ●=未研磨 単位:mm

サイズ 厚さx 幅	mm	Kg/P	コールド	HL	#400 研磨	HOT
9x60	4000	17.1	●	●		●
9x65	4000	18.6	●	●	●	●
	6000	27.8	●	●		●
9x75	4000	21.4	●	●	●	●
	6000	32.1	●	●		●
9x90	4000	25.7	●	●		●
9x100	4000	28.6	●	●		●
	6000	42.8	●	●		●
9x125	4000	35.7	●	●		●
	6000	53.5				●
9x150	4000	42.8	●	●		●
	6000	64.2				●
9x200	4000	57.2	●	●		●
9x250	4000	71.2	●	●		●
9x300	4000	85.6	●	●		●
10x10	4000	3.17	●	●	●	●
10x15	4000	4.76	●	●		●
10x19	4000	6.04	●	●		●
10x20	4000	6.36	●	●	●	●
10x25	4000	7.92	●	●	●	●
10x30	4000	9.52	●	●	●	●
10x32	4000	10.2	●	●	●	●
10x35	4000	11.1				●
10x38	4000	12.0	●	●	●	●
10x40	4000	12.7	●	●	●	●
10x50	4000	15.8	●	●	●	●
10x65	4000	20.6	●	●	●	●
10x75	4000	23.8	●	●	●	●
10x100	4000	31.7	●	●		●
10x125	4000	39.6	●	●		●
10x150	4000	47.6	●	●		●
10x200	4000	63.6	●	●		●
10x250	4000	79.2	●	●		●
10x300	4000	95.2	●			●
12x12	4000	4.56	●	●	●	●
12x14	4000	5.32	●			●
12x15	4000	5.72				●
12x16	4000	6.08	●	●		●
12x19	4000	7.24	●	●		●
12x20	4000	7.60	●	●	●	●
12x25	4000	9.52	●	●	●	●
12x28	4000	10.6				●
12x30	4000	11.4	●	●	●	●
12x32	4000	12.2	●	●	●	●

サイズ 厚さx 幅	mm	Kg/P	コールド	HL	#400 研磨	HOT
12x32	6000	18.3	●	●		
12x35	4000	13.3	●	●		●
12x38	4000	14.5	●	●	●	●
	6000	21.7	●	●		●
12x40	4000	15.2	●	●	●	●
	6000	22.9	●	●		●
12x50	4000	19.0	●	●	●	●
	6000	28.6	●	●		●
12x65	4000	24.8	●	●	●	●
	6000	37.1	●	●		●
12x70	4000	26.6				●
12x75	4000	28.6	●	●	●	●
	6000	42.8	●	●		●
12x90	4000	34.2	●	●		●
12x100	4000	38.1	●	●		●
	6000	57.1	●	●		●
12x125	4000	47.6	●	●		●
	6000	71.4				●
12x150	4000	57.2	●	●		●
	6000	85.8				●
12x200	4000	76.0	●	●		●
12x250	4000	95.2	●	●		●
12x300	4000	114	●			●
13x13	4000	5.36	●	●	●	●
14x14	4000	6.20	●	●	●	●
15x15	4000	7.12	●	●	●	●
16x16	4000	8.12	●	●	●	●
16x19	4000	9.64	●	●		●
16x20	4000	10.2	●	●	●	●
16x25	4000	12.7	●	●	●	●
16x30	4000	15.2				●
16x32	4000	16.2	●	●	●	●
16x35	4000	17.8				●
16x38	4000	19.3	●	●	●	●
16x40	4000	20.3	●	●		●
16x50	4000	25.4	●	●	●	●
	6000	38.0				●
16x65	4000	33.0	●	●		●
	6000	49.5				●
16x75	4000	38.1	●	●		●
	6000	57.1				●
16x90	4000	45.6				●